Bus Garage

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT NAME: 4092 Ultraplex Grease No. 2

MANUFACTURER'S NAME:

ET - Petroleum Solutions Inc.

809 Douglas Street P.O. Box 389

Bremen, IN 46506

EMERGENCY

PHONE NUMBER:

1-888-505-0390

NFPA CODE: Health: 2

Reactivity: 0

HMIS CODE: Health: 2

Fire: 1

Fire: 1

Reactivity: 0

SECTION II - INGREDIENTS & EXPOSURE LIMITS

COMPONENT(S)

(CHEMICAL & COMMON NAME)

OSHA PEL

ACGIH TLV

OTHER EXPOSURE

LIMITS

CAS. NO.

The precise composition of this mixture is proprietory information. A more complete disclosure will be provided to a physician or nurse in the event of a medical emergency.

SECTION III - HEALTH HAZARD INFORMATION (OVEREXPOSURE)

ACUTE:

May cause eye or skin irritation.

CHRONIC:

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading

to irritation and dermatitis.

EYE CONTACT:

May cause irritation which may cause headaches, dizziness, nausea, discomfort, tearing or

blurring of vision.

SKIN CONTACT:

May cause irritation.

INHALATION:

Vapor inhalation under ambient conditions is normally not a problem.

INGESTION:

No information available.

CHEMICAL LISTED AS

OSHA: No

CARCINOGEN OR

National Toxicology Program: No

POTENTIAL CARCINOGEN: I.A.R.C. Monographs: No

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:

Flush immediately with clear water for at least 15 minutes. See a physician if irritation persists.

SKIN CONTACT:

Remove any contaminated clothing and wash skin thoroughly with soap and water. Launder

contaminated clothing before reuse.

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. If

breathing is difficult, give oxygen. Get medical attention.

INGESTION:

Do not induce vomiting. Keep warm and quiet. Get prompt medical attention. Never give

anything by mouth to an unconscious person.

SECTION V - PHYSICAL & CHEMICAL CHARACTERISTICS

BOILING POINT:

>600° F

MELTING POINT:

Not Available

SPECIFIC GRAVITY (H20=1): 0.92 @ 16° C

VAPOR PRESSURE (mmHg): Not available

VAPOR DENSITY (Air=1):

Not available

SOLUBILITY IN WATER: Negligible

APPEARANCE AND ODOR:

Purple Semi-Solid Bland

REACTIVITY IN WATER:

SECTION VI - PHYSICAL HAZARDS (REACTIVITY DATA)

STABILITY:

Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION

PRODUCTS:

Fumes, smoke, carbon monoxide and other decomposition products, in the case of incomplete combustion.

HAZARDOUS

POLYMERIZATION: Will Not Occur

CONDITIONS TO AVOID:

None

SECTION VII - FIRE & EXPLOSION DATA

TYPICAL FLASH POINT:

430° F

METHOD USED: D-92

FLAMMABLE LIMITS IN AIR % BY VOLUME: LEL - N/A UEL - N/A

AUTO-IGNITION TEMPERATURE: 470° F

EXTINGUISHER MEDIA:

Dry chemical, water spray fog, foam, carbon dioxide, earth or sand.

SPECIAL FIRE FIGHTING

PROCEDURES:

Use water spray to cool fire exposed surfaces and to protect personnel. Respiratory and eye protection are required for all fire fighting personnel. Water may cause frothing.

UNUSUAL FIRE &

EXPLOSION HAZARDS:

None.

SECTION VIII - SPECIAL PRECAUTIONS & SPILL/LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN

IN HANDLING & STORAGE:

Keep containers closed when not in use. Store in well ventilated area away from sparks,

flame, heat, and oxidizing and reducing agents. Store at ambient temperatures. Wash

thoroughly after handling.

SPILL PROCEDURES:

Absorb with sand or inert material. Sweep or scoop up and remove.

WASTE DISPOSAL METHODS

(Consult federal, state and local

regulations):

Material should be disposed of in a manner which is acceptable by federal, state, and

local regulations.

SECTION IX - SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

RESPIRATION PROTECTION: None.

FOR HANDS OR BODY:

Use chemical-resistant gloves, apron, or other impervious clothing to avoid staining of

regular clothing or irritation which could result in prolonged or repeated skin contact.

Wash contaminated area thoroughly.

FOR EYES:

Use splash goggles or face shield.

VENTILATION:

Use with adequate ventilation.

SECTION X - TRANSPORTATION & LABELING

U.S. DOT BULK SHIPPING DESCRIPTION:

Not Regulated

U.S. DOT NON-BULK SHIPPING DESCRIPTION:

Not Regulated

SECTION XI - REGULATORY INFORMATION

U.S. TSCA INVENTORY:

All components of this material are on the US TSCA Inventory.

SARA EXTREMELY

HAZARDOUS SUBSTANCES:

This product does not contain greater than 1.0% of any chemical substance on the

SARA Extremely Hazardous Substances list.

SARA SECTION 313:

2.5% Zinc Compounds

DATE PREPARED: 11/15/10

SUPERSEDES ISSUE DATE: All

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of seller's knowledge; however, seller makes no warranty whatsoever, expressed, implied or of merchantability regarding the accuracy of such data or the results to be obtained from the use thereof, seller assumes no responsibility for injury to buyer or to third persons or for any damage to any property and buyer assumes all such risks.