FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

Material Safety Data Sheet (MSDS)

MSDS #: 683.80

Revision Date: October 8, 2002

Section 1 — Chemical Product and Company Identification

Selenium

Flinn Scientific, Inc. P.O. Box 219 Batavia, IL 60510 (800) 452-1261

CHEMTREC Emergency Phone Number: (800) 424-9300

Section 2 — Composition, Information on Ingredients

Selenium

CAS#: 7704-34-9

Section 3 — Hazards Identification

Reddish black powder. Faint odor of rotten eggs.

Slightly toxic by ingestion, inhalation or absorbed through the skin. Body tissue irritant. Avoid all body tissue contact.

FLINN AT-A-GLANCE

Health-1 Flammability-1 Reactivity-0 Exposure-1 Storage-0

0 is low hazard, 3 is high hazard

Section 4 — First Aid Measures

Call a physician, seek medical attention for further treatment, observation and support after first aid.

Inhalation: Remove to fresh air at once. If breathing has stopped give artificial respiration immediately.

Eye: Immediately flush with fresh water for 15 minutes.

External: Wash continuously with fresh water for 15 minutes.

Internal: Do not induce vomiting; give 2-4 cups of milk or water. Call a physician or poison control at once.

Section 5 — Fire Fighting Measures

Combustible powder.

NFPA CODE

Fire and explosion risk in finely divided form. When heated, it will burn and emit highly toxic SeOx

Fire Fighting Instructions: Use triclass, dry chemical fire extinguisher. Firefighters should wear PPE and SCBA with full facepiece operated in positive pressure mode.

Section 6 — Accidental Release Measures

Restrict unprotected personnel from area. Sweep up, place in sealed bag or container and dispose. Ventilate area and wash spill site after material pickup is complete. See Sections 8 and 13 for further information.

Section 7 — Handling and Storage

Flinn Suggested Chemical Storage Pattern: Inorganic #10. Store with sulfur and phophorus.

<u>Section 8 — Exposure Controls , Personal Protection</u>

Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, chemical-resistant gloves and chemical-resistant apron. Use exhaust ventilation to keep airborne concentrations low.

FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

Material Safety Data Sheet (MSDS)

Selenium

MSDS #: 683.80

Revision Date: October 8, 2002

Section 9 — Physical and Chemical Properties

Reddish black powder. Solubility: Insoluble in water.

Formula: Se

Formula Weight: 78.96

Specific Gravity: 4.81 Melting Point: 217 C

Section 10 — Stability and Reactivity

Avoid contact with oxidizers and contact with acids.

Shelf Life: Indefinite.

<u>Section 11 — Toxicological Information</u>

Acute effects: Slightly toxic ORL-RAT LD50: 6700 mg/kg

Chronic effects: Dermatitis, loss of hair IHL-RAT LC50: N.A.

Target organs: Spleen, lungs, skin, liver EYE-HUM:

N.A. = Not available, not all health aspects of this substance have been fully investigated.

Section 12 — Ecological Information

Section 13 — Disposal Considerations

Please consult with state and local regulations. Flinn Suggested Disposal Method #26a is one option.

Section 14 — Transport Information

Shipping Name: Selenium

Hazard Class: 9 UN Number: N/A = Not applicable

Section 15 — Regulatory Information

TSCA-listed, EINECS-listed (231-957-4).

Section 16 — Other Information

Consult your copy of the Flinn Scientific Catalog/Reference Manual for additional information about laboratory chemicals. This Material Safety Data Sheet (MSDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. Flinn Scientific Inc. assumes no legal responsibility for use or reliance upon this data.

FLINN SCIENTIFIC INC.

"Your Safer Source for Science Supplies"

Flinn MSDS Prevent Chemical Accidents

flinn@flinnsci.com www.flinnsci.com P.O. Box 219 Batavia IL 60510 (800) 452-1261 Fax (866) 452-1436